




|  TSURUMI PUMP | KRS2 - SERIES HIGH VOLUME - DEWATERING PUMP | SPECIFICATIONS |
|--|--|---|
| <p>■ FEATURES</p> <ol style="list-style-type: none"> 1. Semi-open, Mixed Flow, impeller, with replaceable adjustable wear plate, increases wear resistance when pumpage contains abrasive particles. 2. Double inside mechanical seals with silicon carbide faces, (both top and bottom) running in an oil filled chamber and further protected by a lip seal running against a replaceable, 430 stainless steel shaft sleeve, provides for the most durable seal design available. 3. Highly efficient, continuous duty air filled, copper wound motor with class E, B, F insulation minimizes the cost of operation. 4. Double shielded, permanently lubricated, high temperature C3 ball bearings, rated for a B-10 life of 60,000 hours, extend operational life. | <ol style="list-style-type: none"> 5. Top discharge, flow-thru design enables operation at low water levels for extended periods. 6. 4 - pole motor increases product life and offers greater convenience. 7. Agitator installed on the motor shaft extension forcibly agitates the fluid for easy and efficient transmission of sludge and slime. (KRS2-80/-100/-150/KRS-200/KRS822L-SK)) <p>■ APPLICATIONS</p> <ol style="list-style-type: none"> 1. Commercial, industrial wastewater and construction site drainage. 2. Effluent transfer. 3. Decorative waterfalls and fountains. 4. Raw water supply from rivers or lakes. |    |
| <p>■ SPECIFICATIONS</p> <p>Discharge Size Horsepower Range Performance Range Capacity Head Maximum water temperature Materials of Construction Casing Impeller Agitator Shaft Motor Frame Fasteners Mechanical Seal Elastomers Impeller Type Solids Handling Capability Bearings Motor Nomenclature Type, Speed, Hz. Voltage, Phase Insulation Accessories Operational Mode</p> | <p>■ STANDARD</p> <p>3 ~ 14" NPT (80 ~ 350 mm) 3 ~ 50 HP. (2.2 ~ 37 kW) 66.0~4359.0 GPM.(0.25~16.50 m³/min) 16.4 ~ 113.0 Ft. (5.0 ~ 34.4 m) 104 °F. (40 °C.)</p> <p>Cast Iron Ductile Cast Iron , High Chrome Cast Iron (KRS2-80/-100/-150/KRS-200/KRS822L-SK) 420 Stainless Steel Cast Iron 304 Stainless Steel Silicon Carbide NBR (Nitrile Butadiene Rubber) Semi-open , Mixed Flow ,with Agitator 0.472 - 1.97" (12.0 - 50.0mm)</p> <p>Prelubricated, Double Shielded</p> <p>Air Filled, 1800 RPM, 60 Hz. 208/230/460/575 V., 3 Phase Class E, F, B</p> <p>Submersible Power Cable 50' (15.0 m)</p> <p>Manual</p> | <p>■ OPTIONS</p> <p>Length as Required</p> <p>TS-301 Float Switch</p> |

**TSURUMI PUMP****KRS - SERIES****HIGH VOLUME - DEWATERING & AGITATOR PUMPS****PERFORMANCE
CURVE****GROUP PERFORMANCE RANGE****Note**

Ex.



**TSURUMI PUMP**

KRD - SERIES

HIGH VOLUME - AGITATOR PUMPS

**PERFORMANCE
CURVE**



| MODEL | BORE | HP | kW | RPM | SOLIDS DIA. | LIQUID | SG. | VISCOSITY | TEMP. |
|-----------------------------|---------|-----------------|------------------------|----------|-----------------|-----------------|------------|-----------|-------|
| KRD35.5 -61 | 3"/80mm | 7.5 | 5.5 | 1733 | 1.18"/30mm | Water | 1.0 | 1.123cSt. | 60°F |
| PUMP TYPE | PHASE | VOLTAGE | AMPERAGE | HZ | STARTING METHOD | INS. CLASS | | | |
| High Volume - Agitator Pump | 3 | 208-230/460/575 | 21.4-20.5 / 10.3 / 8.3 | 60 | Direct On Line | F | | | |
| CURVE No. | DATE | PHASE | VOLTAGE | AMPERAGE | HZ | STARTING METHOD | INS. CLASS | | |
| - | - | - | - | - | - | - | - | | |



**TSURUMI PUMP**

KRD SERIES

HIGH VOLUME - AGITATOR PUMPS

DIMENSIONS**KRD35.5 -61**

C.W.L. :Continuous running Water Level


DIMENSIONS:USCS (Inch)

| Model | HP | NOM. SIZE | Pump & Motor | | | | | | | | | C.W.L. | *Wt. |
|-------------|-----|--------------|--------------|---------|---------|--------|--------|----------|-------|-------|---------|--------|--------|
| | | | A | A1 | A2 | B | B1 | D | D1 | D2 | H | W1 | (lbs.) |
| KRD35.5 -61 | 7.5 | 3" | 13 13/16 | 10 3/16 | 3 15/16 | 30 5/8 | 28 1/8 | 12 13/16 | 6 1/4 | 6 5/8 | 32 1/16 | 10 3/8 | 236 |

DIMENSIONS:METRIC (mm)

*Excluding Cable

| Model | kW | NOM. SIZE | Pump & Motor | | | | | | | | | C.W.L. | *Wt. |
|-------------|-----|--------------|--------------|-----|-----|-----|-----|-----|-----|-----|-----|--------|------|
| | | | A | A1 | A2 | B | B1 | D | D1 | D2 | H | W1 | (kg) |
| KRD35.5 -61 | 5.5 | 80 | 351 | 259 | 100 | 778 | 715 | 326 | 158 | 168 | 815 | 265 | 107 |

KRD35.5 -61


| ITEM# | DESCRIPTION | MAIN MATERIAL / NOTE | ASTM, AISI CODE | RELATED DIN CODE | Q'TY |
|-------|------------------|------------------------------------|-------------------------|--------------------------|------|
| 1 | Power Cable | Chloroprene Sheath AWG12/4-50ft | | | 1 |
| 6 | Stuffing Box | Cast Iron | A48M Class30B | EN 1561 GJL-200 | 1 |
| 20 | Pump Casing | Cast Iron | A48M Class30B | EN 1561 GJL-200 | 1 |
| 21 | Impeller | High Chrome Cast Iron | A532 Class III Type A | DIN 1695 G-X260Cr27 | 1 |
| 22 | Suction Cover | Cast Iron | A48M Class30B | EN 1561 GJL-200 | 1 |
| 23 | Suction Strainer | Steel (Cold Rolled) + Steel Pipe | A109/A1008 + A53 Type F | EN 10130 + DIN 1615 St33 | 1 |
| 24A | Agitator | High Chrome Cast Iron | A532 Class III Type A | DIN 1695 G-X260Cr27 | 1 |
| 24B | Clutch | Ductile Cast Iron | A536 65-45-12 | EN 1563 GJS-450-10 | 1 |
| 25 | Mechanical Seal | Silicon Carbide / H-30 | | | 1 |
| 26 | Oil Seal | NBR / TC-355511 | | | 1 |
| 30 | Oil Lifter | PBT Plastic W/(GF+MD)40 | | | 1 |
| 32 | Hose Coupling | Cast Iron / NPT 3" | A48M Class30B | EN 1561 GJL-200 | 1 |
| 33 | Suction Plate | High Chrome Cast Iron | A532 Class III Type A | DIN 1695 G-X260Cr27 | 1 |
| 35 | Oil Plug | Stainless Steel | S 30400 | 1.4301 | 1 |
| 36 | Lubricant | Turbine Oil ISO VG32 or SAE 10W-20 | | | |
| 50 | Motor Bracket | Cast Iron | A48M Class30B | EN 1561 GJL-200 | 1 |
| 52A | Upper Bearing | #6305ZC3 | | | 1 |
| 52B | Lower Bearing | #6308ZC3 | | | 1 |
| 53 | Motor Protector | | | | 1 |
| 54 | Shaft | Stainless Steel | S 42000 | 1.4028 | 1 |
| 55 | Rotor | | | | 1 |
| 56 | Stator | | | | 1 |
| 60 | Bearing Housing | Cast Iron | A48M Class30B | EN 1561 GJL-200 | 1 |
| 64 | Motor Housing | Cast Iron | A48M Class30B | EN 1561 GJL-200 | 1 |
| 68 | Handle | Steel (Cold Rolled) + Steel Pipe | A109/A1008 + A53 Type F | EN 10130 + DIN 1615 St33 | 1 |
| 71 | Shaft Sleeve | Stainless Steel | S 40300 | 1.4000 | 1 |



KRS - SERIES HIGH VOLUME - DEWATERING PUMPS

SAMPLE SPECIFICATIONS

1. SCOPE OF SUPPLY -

Furnish and install TSURUMI Model _____ Submersible Pump(s).
Each unit shall be capable of delivering _____ GPM (_____ m³/min) at _____ Feet (_____ m) TDH.
The pumps shall be designed to pump waste water, without damage during operation. The pump(s) shall be designed so that the shaft power required (BHP)/(kW) shall not exceed the motor rated output throughout the entire operating range of the pump performance curve. Pump(s) shall be of the top discharge flow through design.

2. MATERIALS OF CONSTRUCTION -

Construction of major parts of the pumping unit(s) shall be as follows: Pump casing shall be gray cast iron, ASTM A48 CLASS 30B. Motor frame shall be gray cast iron. Field adjustable/replaceable wear plate shall be gray cast iron, ASTM A48 CLASS 30B or high chrome cast iron (40 HP and above). Impellers on units up to 30 HP / 8" bore shall be of the multi-vane semi-open design, and shall be ductile cast iron (ASTMA536 100-70-03). Impeller on KRS1022 shall be of the multi-vane enclosed design, and shall be ductile cast iron (ASTMA536 100-70-03). Impellers on KRS-1230/1437 shall be of the multi-vane semi-open design, and shall be high chrome cast iron. Impellers shall be equipped with back pump out vanes, slip fit to the shaft and key driven. Internal and external surfaces coming into contact with the pumpage shall be protected by a fused polymer coating. All exposed fasteners shall be stainless steel. All units shall be furnished with _____" NPT discharge connector.

3. MECHANICAL SEAL -

All units shall be furnished with a dual inside mechanical shaft seal located completely out of the pumpage, running in a separate oil filled chamber and further protected by an exclusionary oil seal located between the bottom seal faces and the fluid being pumped. The oil chamber shall be fitted with a device that shall provide positive lubrication of the top mechanical seal, (down to one third of the standard oil level). The device shall not consume any additional electrical power. Mechanical seals shall rated to preclude the incursion of water up to 42.6 PSI. (98.4 Ft.) submergence. Units shall be have silicon carbide upper and lower mechanical seal faces. Mechanical seal hardware shall be stainless steel.

4. MOTOR-

The pump motor(s) shall be _____ HP., _____ kW., _____ V., 60 Hz. 3 Phase and shall be NEMA MG-1, Design Type B equivalent. Motor(s) shall be rated at _____ full load amps. Motor(s) shall have a 1.15 service factor and shall be rated for 20 starts per hour. Motor(s) shall be air filled, copper wound, class F, B or E insulated with built in thermal protection for each winding. Motor shaft shall be 420 stainless steel, fitted with a replaceable 403 stainless steel shaft sleeve and shall be supported by two permanently lubricated, high temperature ball bearings, with a B-10 life rating at best efficiency point of 60,000 hours. Bearings on units up to 20 Hp shall be single row, double shielded, C3, deep groove type ball bearing. On units 25 Hp. (19 kW) and above, the bottom bearing shall be two row, double shielded, C3, deep groove type ball bearing, and the top bearing shall be single row, double shielded, C3, deep groove type ball bearing. Motors shall be D.O.L. or star-delta start (40 and 50 Hp), and shall be suitable for across the line start or variable speed applications, utilizing a properly sized variable frequency drive.

5. POWER CABLE AND CABLE ENTRANCE -

The pump power cable shall be suitable for submersible pump applications and shall be field replaceable utilizing standard submersible pump cable. The cable entrance shall incorporate built in strain relief and a combination three way mechanical compression sealing with a fatigue reducing boot (up to 30 Hp). The cable entrance assembly shall contain a anti-wicking block to eliminate water incursion into the motor due to capillary wicking should the power cable be accidentally damaged.