



AB - SERIES PROPELLER TYPE - DEWATERING PUMPS

SPECIFICATIONS

■ FEATURES

1. Axial flow, cast iron propeller provides for high efficiency, high volume pumping at low head.
2. Highly efficient, continuous duty air filled, copper wound motor with class E, insulation minimizes the cost of operation.
3. Built in thermal protection prevents motor failure due to overloading, accidental run-dry and single phasing in three phase units.
4. Double inside mechanical seals with silicon carbide faces, running in an oil filled chamber and further protected by a lip seal running against a replaceable, 430 stainless steel shaft sleeve, provides for the most durable seal design available.
5. Double shielded, permanently lubricated, high temperature C3 ball bearings rated for a B-10 life of 60,000 hours provide for extended operational life.
6. AB Series has non toxic White Mineral Oil.

■ APPLICATIONS

1. Residential, commercial, industrial wastewater and site drainage.
2. Decorative waterfalls and fountains.
3. Raw water supply from lakes or rivers.
4. Tail Water Pump.



■ SPECIFICATIONS

Discharge Size
Horsepower Range
Performance Range Capacity
Head
Maximum water temperature
Materials of Construction
Casing
Impeller
Shaft
Motor Frame
Fasteners

Mechanical Seal
Elastomers

Impeller Type
Solids Handling Capability

Bearings

Motor Nomenclature
Type, Speed, Hz.
Voltage, Phase

Insulation

Accessories

Operational Mode

■ STANDARD

4"~6" NPT. (100 - 150 mm)
1/ 2 - 2 Hp. (0.4 - 1.5 kW)
92.5 - 666.0 GPM. (0.35 - 2.52 m³/min)
2.5 - 13.0 Ft. (0.75 - 3.96 m)
104° F. (40° C.)

Cast Iron
Cast Iron
403 Stainless Steel
Steel Plate , Cast Iron
304 Stainless Steel

Silicon Carbide
NBR (Nitril Buna Rubber)

Axial Flow, High Volume
0.118 - 0.315" (3.0 - 8.0mm)

Pre-lubricated, Double Shielded


Air Filled, 3600 /1800 Rpm, 60 Hz.
115 / 230 V., 1 Phase (1/ 2 Hp)
208-220 / 460V ., 3Phase (1/ 2 - 2 Hp.)
Class E

Submersible Power Cable
16 - 32' (5 - 10 m)
Manual

■ OPTIONS

Nema 3R inverter available for
230 V., 1 Ph. operation from
1~2 Hp.

Length as Required


**TSURUMI PUMP****AB - SERIES**
PROPELLER TYPE - DEWATERING PUMP**PERFORMANCE**
RANGE**GROUP PERFORMANCE RANGE**




AB - SERIES PROPELLER TYPE - DEWATERING PUMPS

PERFORMANCE CURVE

MODEL		BORE	HP	KW	RPM	SOLIDS DIA		LIQUID		SG.	VISCOSITY	TEMP.
150AB41.5-61		6"/150mm	2	1.5	1730	0.118"/3mm		Water		1.0	1.123 cSt.	60°F
PUMP TYPE		PHASE	VOLTAGE		AMPERAGE		HZ	STARTING METHOD			INS. CLASS	
Propeller Type Dewatering Pump		3	208-220 / 460		6.7-6.3 / 3.4		60	Direct On Line			E	
CURVE No.	DATE	PHASE	VOLTAGE		AMPERAGE		HZ	STARTING METHOD			INS. CLASS	
-	-	-	-		-		-	-			-	



150AB41.5-61


C.W.L. : Continuous running Water Level

DIMENSIONS:USCS (Inch)

Model	HP	NOM. SIZE	Pump & Motor					C.W.L.	Wt. (lbs.)
			D	D1	D2	B	H	W1	
150AB41.5-61	2	6"	10 11/16	5 3/8	5 3/8	21 13/16	22 13/16	11 3/4	97

DIMENSIONS:METRIC (mm)


Model	kW	NOM. SIZE	Pump & Motor					C.W.L.	Wt. (kg)
			D	D1	D2	B	H	W1	
150AB41.5-61	1.5	150	272	136	136	554	579	300	44



AB - SERIES **PROPELLER TYPE - DEWATERING PUMPS**

SECTIONAL VIEW

150AB41.5-61



PART#	DESCRIPTION	MAIN MATERIAL / NOTE	ASTM, AISI CODE	RELATED DIN CODE	QTY
1	Power Cable	PVC Sheath AWG16/4-32ft			1
20	Pump Casing	Cast Iron	A48M Class30B	EN 1561 GJL-200	1
21	Impeller	Cast Iron	A48M Class30B	EN 1561 GJL-200	1
23	Suction Strainer	Stainless Steel	S 30400	1.4301	1
25	Mechanical Seal	Silicon Carbide / H-20A			1
29	Oil Casing	Cast Iron	A48M Class30B	EN 1561 GJL-200	1
30	Oil Lifter	PBT Plastic w/(GF+MD)40			1
32	Discharge Connection	Cast Iron / NPT 6"	A48M Class30B	EN 1561 GJL-200	1
35	Oil Plug	Stainless Steel	S 30400	1.4301	1
36	Lubricant	White Mineral Oil ISO VG32			
51	Motor Head Cover	Cast Iron	A48M Class30B	EN 1561 GJL-200	1
52A	Upper Bearing	#6303ZZC3			1
52B	Lower Bearing	#6305ZZC3			1
53	Motor Protector				1
54	Shaft	Stainless Steel	S 40300	1.4000	1
55	Rotor				1
56	Stator				1
64	Motor Housing	Cast Iron	A48M Class25B	EN 1561 GJL-150	1
65	Outer Cover	Stainless Steel	S 30400	1.4301	1
68	Handle	Cast Iron	A48M Class30B	EN 1561 GJL-200	2