



BK - SERIES SEWAGE & WASTEWATER PUMPS

SPECIFICATIONS

■ FEATURES

1. Internal cooling jacket offers continued cooling during low sump levels or dry pit Pumping.
2. Enclosed Multi-vane, impellers, with field adjustable / replaceable wear plate provides for high wear resistance and enhanced solids handling capability.
3. Highly efficient, continuous duty air filled, copper wound motor with class F insulation minimizes the cost of operation.
4. Built in thermal protection prevents motor failure due to overloading, accidental run-dry and single phasing in three phase units.
5. Double inside mechanical seals with silicon carbide faces, running in an oil filled chamber, equipped with an oil lifter,, and further protected by an exclusionary oil -

- Seal(s), provides for the most durable seal design available.

6. Double shielded, permanently lubricated, high temperature C3 ball bearings rated for a B-10 life of 60,000 hours provide for extended operational life.

■ APPLICATIONS

1. Commercial, Industrial sewage, wastewater, or effluent transfer.
2. Decorative fountains and aquiculture .
3. Raw water supply from rivers or lakes.
4. Dry pit sump design available.



■ SPECIFICATIONS

Discharge Size
Horsepower Range
Performance Range, Capacity
Head
Maximum water temperature
Materials of Construction
Casing
Impeller
Shaft
Motor Frame
Fasteners

Mechanical Seal
Elastomers

Impeller Type
Solids Handling Capability

Bearings

Motor Nomenclature
Type, Speed, Hz.

Voltage, Phase

Insulation
Accessories

Operational Mode

■ STANDARD

6" ~ 16" (150 ~ 400 mm)
30 Hp. ~ 60 Hp. (22 kW ~ 45 kW)
429 ~ 6340 G.P.M. (1.6 ~ 24.0 m³/min)
10.7 Ft.~154.2 Ft. (3.3 ~ 47.0m)
104° F. (40° C.)

Cast Iron, ASTM 48 Class 35
Cast Iron, ASTM 48 Class 35
420 Stainless Steel
Cast Iron, ASTM 48 Class 30
304 Stainless Steel

Silicon Carbide
NBR (Nitril Buna Rubber)

Semi-open, Enclosed, solids handling.
1.57" ~ 4.25" (40 ~ 108 mm)

Pre-lubricated, Double Shielded

Air Filled,
3600, 1800, 1200 & 900 Rpm, 60 Hz.

460 or 575 V., (3 Phase)


Class F
Submersible Power Cable 32' (10 m)

Manual

■ OPTIONS

Dry-Pit

Length as required.
TO/TOS Slide Rail System

**GROUP PERFORMANCE RANGE**






BK - SERIES

SEWAGE & WASTEWATER PUMPS



PERFORMANCE
CURVE

MODEL		BORE	HP	KW	RPM	SOLIDS DIA.	LIQUID	SG.	VISCOSITY	TEMP.
(TOS)150BK422-64		6"/150mm	30	22	1750	2.95"/75mm	Water	1.0	1.123cSt.	60°F
PUMP TYPE		PHASE	VOLTAGE		AMPERAGE		HZ	STARTING METHOD		INS. CLASS
Sewage & Wastewater		3	460/575		39 / 31.5		60	Star-Delta		F
CURVE No.	DATE	PHASE	VOLTAGE		AMPERAGE		HZ	STARTING METHOD		INS. CLASS
-	-	-	-		-		-	-		-



**TSURUMI PUMP**
B-SERIES
SEWAGE & WASTEWATER PUMPS
SECTIONAL VIEW
150BK422 -64
200BK422H -63

PART#	DESCRIPTION	MAIN MATERIAL / NOTE	RELATED ASTM,AISI CODE	RELATED EN CODE	QTY
1	Power Cable	Chloroprene Sheath AWG 6/4-32ft			1
	Power Cable	Chloroprene Sheath AWG 6/3-32ft			1
	Control Cable	Chloroprene Sheath AWG 14/4-32ft			1
6	Stuffing Box	Cast Iron	A48M Class30B	EN 1561 GJL-200	2
20	Pump Casing	Cast Iron	A48M Class35B	EN 1561 GJL-250	1
21	Impeller	Cast Iron	A48M Class35B	EN 1561 GJL-250	1
22	Suction Cover	Cast Iron	A48M Class35B	EN 1561 GJL-250	1
23	Suction Strainer	Ductile Cast Iron	A536 80-55-06	EN 1563 GJS-500-7	1
25	Mechanical Seal	Silicon Carbide / H-60			1
26A	Oil Seal	NBR / TC659013			1
26B	Oil Seal	NBR / TC10012513			1
29A	Casing Cover	Cast Iron	A48M Class30B	EN 1561 GJL-200	1
29B	Oil Casing	Cast Iron	A48M Class35B	EN 1561 GJL-250	1
29C	Casing Plate	Cast Iron	A48M Class35B	EN 1561 GJL-250	1
30	Oil Lifter	Steel (Cold Rolled)	A109/A1008	EN 10130	1
31	Wear Ring	Cast Iron	A48M Class30B	EN 1561 GJL-200	1
35A	Oil Plug	Stainless Steel	S 30400	1.4301	2
35B	Oil Plug	Stainless Steel	S 30400	1.4301	1
35C	Drain Plug	Stainless Steel	S 30400	1.4301	1
36	Lubricant	Turbine Oil ISO VG32 or SAE 10W-20			
37	Discharge Bend	Cast Iron	A48M Class30B	EN 1561 GJL-200	1
46A	Air Release Valve	Nylon			1
46B	Air Release Valve	Stainless Steel	S 30400	1.4301	1
48	Companion / Welded Flange	Cast Iron / 6" NPT Companion or 8" Welded	A48M Class30B	EN 1561 GJL-200	1
50	Motor Bracket	Cast Iron	A48M Class30B	EN 1561 GJL-200	1
52A	Upper Bearing	#6309ZZC3			1
52B	Lower Bearing	#6314ZZD2C3			1
53	Motor Protector				3
54	Shaft	Stainless Steel	S 42000	1.4021	1
55	Rotor				1
56	Stator				1
60	Bearing Housing	Cast Iron	A48M Class30B	EN 1561 GJL-200	1
64	Motor Housing	Cast Iron	A48M Class30B	EN 1561 GJL-200	1
65	Outer Cover	Steel	A283 Grade D	EN 10025 S275	1
72	Lifting Lug Bolt	Stainless Steel	S 30400	1.4301	2
80	Cooling Pipe Set	Steel	A283 Grade D	EN 10025 S275	1
90	Leak Sensor (Float)				1
217	Fixing Plate	Cast Iron	A48M Class30B	EN 1561 GJL-200	1

**TSURUMI PUMP**
B-SERIES
SEWAGE & WASTEWATER PUMPS
DIMENSIONS**150BK422 -64**

C.W.L. :Continuous running Water Level

DIMENSIONS:USCS(Inch)

Model	HP	NOM. SIZE	Pump & Motor									C.W.L.	*Wt.
			A	A1	A2	A3	B	D	D1	D2	H	W1	(lbs.)
150BK422 -63	30	6"	38 7/8	22 3/4	10 5/8	15 9/16	22 1/16	21 1/4	10 5/8	10 5/8	52 1/8	16 3/4	1180

DIMENSIONS:METRIC(mm)

Model	kW	NOM. SIZE	Pump & Motor									C.W.L.	*Wt. (kg)
			A	A1	A2	A3	B	D	D1	D2	H	W1	
150BK422 -63	22	150	988	578	270	395	531	540	270	270	1324	425	535

*Excluding Cable

